

Flat-ribbon conductor - VS-ASI-FC-TPE-UL-BK 1000M - 1434675


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



AS-Interface TPE flat conductor with UL in black, for additional power supply, 2 x 1.5 mm², 1000 m disposable drum



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 349284
GTIN	4046356349284

Technical data

Mechanical characteristics

Number of positions	2
Shielded	no
Type of cable	Flat-ribbon conductor
Cable structure	2x 1.5 mm ²
Duty cycle testing	suitable for drag chain
Length of cable	1000 m

Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C (fixed routing)
	-30 °C ... 105 °C (Flexibly installed)
Ambient temperature (assembly)	-30 °C ... 105 °C
Ambient temperature (storage/transport)	-40 °C ... 105 °C

Material data

Outer sheath, material	TPE
External sheath, color	black RAL 9005
Height	4 mm

Electrical characteristics

Flat-ribbon conductor - VS-ASI-FC-TPE-UL-BK 1000M - 1434675

Technical data

Electrical characteristics

Rated voltage (III/3)	300 V
Rated surge voltage	2 kV

Standards and Regulations

Duty cycle testing	suitable for drag chain
--------------------	-------------------------

Line characteristics

Type of cable	Flat-ribbon conductor
Cable structure	2x 1.5 mm ²
Conductor cross section	1.5 mm ²
AWG power supply	16
Conductor structure, voltage supply	84x 0.15 mm
Core diameter including insulation	2.5 mm
Thickness, insulation	approx. 0.5 mm
Wire colors	brown, blue
External sheath, color	black RAL 9005
Insulation resistance	≥ 1 MΩ*km
Conductor resistance	≤ 13.7 Ω/km
Nominal voltage, cable	300 V
Test voltage, cable	2000 V
Outer sheath, material	TPE
Material conductor insulation	TPE
Conductor material	Bare Cu litz wires
Cable weight	64 kg/km
Smallest bending radius, fixed installation	≥ 6 mm (one-time)
Traversing direction	horizontal, above the broadside
Max. bending cycles	8000000
Bending radius	75 mm
Traversing rate	4 m/s
Acceleration	4 m/s ²
Traversing direction	vertical, above the broadside
Max. bending cycles	10000000
Bending radius	50 mm
Special properties	UL-Style 2103
	CSA-File LL55255-42
Flame resistance	UL 1581, Sec. 1061 (Cable Flame)
	IEC 60332-1-2
Halogen-free	no
Resistance to oil	UL 1581, Sec. 480 (60 °C)
Other resistance	UV resistant
Ambient temperature (operation)	-40 °C ... 105 °C (cable, fixed installation)
	-30 °C ... 105 °C (cable, flexible installation)

Flat-ribbon conductor - VS-ASI-FC-TPE-UL-BK 1000M - 1434675

Technical data

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>