

Dec.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case that the application demands a high level of reliability, such as automotive,
 please contact a company representative for further information.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C	
	OPERATING&STORAGE HUMIDITY RANGE	85%MAX	APPLICABLE CABLE	CABLE DIAMETER : φ8.3~9.3	
	VOLTAGE		CURRENT		
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		X	X	
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△					
REMARK THIS PRODUCT SHALL BE MATED WITH DH3 * B-37S,IT APPLIES TO DH3 * B-37S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS. Unless otherwise specified, refer to JIS C 5402.			APPROVED	KN. ICHIKAWA	10.07.05
			CHECKED	KN. ICHIKAWA	10.07.05
			DESIGNED	TU. TANIGUCHI	10.07.05
			DRAWN	TU. TANIGUCHI	10.07.05
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELG4-126592-00
HRS	SPECIFICATION SHEET		PART NO.	DH-37-CV2B	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL244-0015-9-00	△ 1/