

MODEL: CPI-42533C-120 | **DESCRIPTION:** PIEZO BUZZER INDICATOR
FEATURES

- includes driving circuit
- wire leads
- 12 Vdc rated voltage

**SPECIFICATIONS**

parameter	conditions/description	min	typ	max	units
rated voltage			12		Vdc
operating voltage		6		28	Vdc
current consumption	at rated voltage			13	mA
	continuous tone			11	mA
	slow pulse tone				
rated frequency		2,300	2,800	3,300	Hz
sound pressure level	at 30 cm, rated voltage				
	continuous tone	92			dB
	slow pulse tone	87			dB
tone	continuous (red wire)				
	slow pulse at rated voltage (blue wire)	0.96	1.2	1.44	Hz
dimensions	Ø42.5 x 33.0				mm
weight				38	g
material	ABS UL94 1/16" HB High Heat				
terminal	wire type				
operating temperature		-30		85	°C
storage temperature		-40		95	°C
RoHS	2011/65/EU				

Notes: 1. All specifications measured at 5~35°C, humidity at 45~85%, under 86~106 kPa pressure, unless otherwise noted.


SOLDERABILITY

parameter	conditions/description	min	typ	max	units
hand soldering	for maximum 5 seconds	330		380	°C



MECHANICAL DRAWING

units: mm
tolerance: ± 0.5 mm

wire: UL1007 LF 18 AWG




PERFORMANCE CURVES



PACKAGING

units: mm

Outer Box Size: 310 x 248 x 49 mm
Carton Size: 530 x 330 x 260 mm
Outer Box QTY: 35 pcs per outer box
Carton QTY: 350 pcs per carton



REVISION HISTORY

rev.	description	date
1.0	initial release	04/06/2016
1.01	updated packaging	07/01/2016

The revision history provided is for informational purposes only and is believed to be accurate.



CUI INC[®]

Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.